

20 June 2024

IPAC-16 | Requirements for as-built drawings

Audience: PBS Certifiers Initial effective date: 1 March 2024 Effective date: 16 July 2024

This IPAC provides guidance to PBS Certifiers on the requirements for as-built drawings. It outlines the essential elements that must be included on the drawing while avoiding unnecessary information.

As-built drawing requirements

To ensure compliance, promote consistency in certification submissions, and facilitate the efficient processing of PBS Vehicle Approvals (VAs), PBS Certifiers are required to adhere to the following asbuilt drawing protocol.

Drawing number

Each as-built drawing must contain a drawing title block.

As a *minimum*, the following must be included in the drawing title block:

- a unique drawing number
- revision number
- drawing title
- date
- author.

A drawing frame should be included along with a drawing title block.

Dimension position and font size

Please ensure that the dimensions are clear and readable. Use a sufficiently large font size and ensure a clear position of dimensions.

Captions of as-built drawings are inserted into the VA document, which may affect the quality of the drawing. Please ensure that the drawings are clearly readable to ensure ease of use and interpretation by all parties in the process—operators, drivers, road managers, and Safety Compliance Officers (SCOs).

If the drawing or dimensions are not clearly readable, we may ask you to modify the drawing, increase the font size and/or modify the dimension position.

Lift axle and steer axle

If steer and/or lift axles are fitted to the vehicle, these must be clearly shown on the as-built drawing. For ease of interpretation, it is preferred that the word 'lift' or 'steer' is shown directly beneath the axle.

Exclusion of VINs

As-built drawings must not include Vehicle Identification Numbers (VINs).

The inclusion of VINs on the as-built drawing would require an update to the drawings every time vehicles are added or removed from a VA. It also creates a significant administrative burden for both the NHVR and Certifiers having to cross-check the VINs on the drawings against the Certifier's Certificate. For these reasons, VINs must not be included on the as-built drawing.

Exclusion of Payload Heights

As-built drawings must not include Payload Heights (PH). In this section reference to PHs also includes Tanker Fill Levels.

Maximum allowable PHs are specified in the corresponding PBS Design Approval (DA) and the Operating Conditions of the VA. If PHs in the DA are updated, or if a vehicle combination is recertified against a different dimension set within the DA or a new DA, the corresponding as-built drawings would need to be updated to reflect the new PH limit. For these reasons, PHs must not be included on the as-built drawing.

Exclusion of axle spacings

As-built drawings must not include Axle Spacings used for bridge assessment.

As part of VA processing, the NHVR generates an axle spacings table that is used by the road manager for access or bridge assessment purposes. The NHVR axle spacings table is the primary source of data and should not be duplicated.

Vehicle dimensions as per Design Approval

As-built drawings must mirror the dimensions shown on the relevant Design Approval (DA) drawing. The dimensions shown on the DA have been identified as critical to vehicle performance and, therefore, must be checked and verified at the certification stage.

Additionally, avoid adding dimensions that are not relevant to PBS certification and VA.



Drawing orientation

The front of the vehicle must be oriented towards the left of the page as such:



Floor heights

If the floor height dimension is shown in an unladen condition and the DA permits additional floor height for tyre deflection when unladen, the drawing must include a note 'vehicle unladen'.

Fifth-Wheel Offset direction

For consistency, the following Fifth-Wheel Offset (FWO) direction convention must be used on all drawings.

- The FWO forward of the centre of an axle group can be referred to as a plain number; i.e., a dimension of '200' means the FWO is 200mm forward of the centre of an axle group.
- FWO rear of the centre of an axle group must be clearly labelled as 'lag'.

For example, an FWO range that spans from forward to rear should be labelled as '200 – lag 100' or 'lead 200 – lag 100'.

Unnecessary labelling must not be included

As-built drawings must not include labels other than those required by IPAC-8 - Vehicle labelling requirements.

Exclusion of irrelevant information

Please do not include information not relevant for certification and vehicle approval purposes, such as any disclaimers of it being a *'sales drawing and/or final design may vary from the layout shown'*.

Grandfathering

Previously accepted drawings not conforming to this protocol will continue to be accepted -Certifiers are not required to amend previously submitted drawings.

When modifying previously accepted drawings, i.e. adding prime movers or trailers to existing drawings, these drawings are considered new and, therefore, must conform to this IPAC.

Contact

This IPAC was produced by the PBS Operations Team; for queries, please email pbs@nhvr.gov.au.

IPAC-16: Revision history	
First Published	July 2023
Version 2	October 2023
Version 3	November 2023
Version 4	November 2023
Version 5	February 2024
Version 6	May 2024
Version 7	June 2024

For more information:

Visit: www.nhvr.gov.au Subscribe: www.nhvr.gov.au/subscribe Email: pbs@nhvr.gov.au for Vehicle Approvals Email: pbsdesigns@nhvr.gov.au for Design Approvals Phone: 13 NHVR* (13 64 87) *Standard 13 call charges apply. Please check with your phone provider. © Copyright National Heavy Vehicle Regulator 2020, creativecommons.org/licenses/by-sa/3.0/au Disclaimer: This information is only a guide and should not be relied upon as legal advice.