PBS EXP 16 - 3-axle pm tri semi

Approval under section 9(1)(b)(i) of the Heavy Vehicle (General) National Regulation – Non compliance

| Approval under section 9(1)(b)(i) of the Heavy Vehicle (General) National Regulation – Non compliance | |
|--|---|
| The type of heavy vehicle: | 3-axle pm tri semi (Level 2) |
| The standard/s under the Standards and Vehicle Assessment Rules that a vehicle built to the design may not comply with: | Maximum of Difference (C8b) Standard: 400mm This vehicle design: 500 mm (exceedance of 100mm) |
| Reasons why the non-compliance will not pose any additional risk to safety or infrastructure if the particular conditions are imposed and complied with. | The Regulator undertook a risk assessment before determining its support for the design. The Regulator concluded that although a heavy vehicle built to the design would not comply with Maximum of Difference (C8b) under the Standards and Vehicle Assessment Rules, it would not pose any greater risk than a heavy vehicle that did comply with the standard for the following reasons: |
| | It exceeds the requirements of Low-Speed Swept Path (C7) in a way that offsets the failure to comply with Maximum of Difference (C8b). (Standard: 8.7m; This vehicle: 7.4m) |
| | Because of its 1300mm margin for Low Speed Swept Path (C7), the vehicle will operate comfortably within Level 2, despite its non-compliance with C8b and will require less road space than other vehicles that comply with Level 2 standards. |